

TECHNICAL PROPERTIES

NİLÜFER4040



4036

Nominal height (mm)	Serial number	Water volume (lt./seg.)	Heating surface (sqm/seg.)	90°C-70 °C (Tm=80°C) Heat output /segment (kcal/h)							75 °C-65 °C (Tm=70°C) Heat output/segment (kcal/h)						
				10°C	15°C	18°C	20°C	22°C	24°C	26°C	10°C	15°C	18°C	20°C	22°C	24°C	26°C
300	275	0.082	0.092	48	43	41	39	37	36	34	39	35	32	31	29	28	26
370	345	0.092	0.111	57	52	49	47	45	43	41	47	42	39	37	35	33	31
375	350	0.093	0.112	58	53	50	48	46	43	41	48	42	39	38	36	34	32
425	400	0.100	0.126	65	59	56	53	51	49	47	53	48	44	42	40	38	36
450	425	0.103	0.132	69	63	59	56	54	51	49	56	50	47	44	42	40	38
470	445	0.106	0.138	72	65	61	59	56	53	51	59	52	49	46	44	41	39
525	500	0.114	0.152	81	73	69	66	63	60	58	66	59	55	52	49	47	44
570	545	0.121	0.164	87	79	74	71	68	65	62	71	63	59	56	53	50	47
600	575	0.125	0.172	90	82	77	74	70	67	64	74	66	61	58	55	52	49
750	725	0.146	0.212	109	99	93	89	85	81	78	89	79	74	70	66	63	59
825	800	0.157	0.232	117	107	100	96	92	88	84	96	86	80	76	72	68	64
870	845	0.164	0.244	124	112	105	101	97	92	88	101	90	84	80	76	71	67
900	875	0.168	0.252	127	116	109	104	100	95	91	104	93	86	82	78	74	69
1000	975	0.182	0.279	142	129	121	116	111	106	101	116	104	96	92	87	82	77
1250	1225	0.218	0.345	171	155	146	140	134	128	122	140	125	116	110	104	99	93
1500	1475	0.254	0.412	199	181	170	163	156	149	142	163	145	135	128	122	115	108

NİLÜFER 4040